

“Easy to use and superior safety!”

For 60 years, LOXX® has been an indispensable solution for quickly and securely fastening tarpaulins, sprayhoods, bimini tops and awnings on boats. Whether for sunshades or rain covers, windbreaks and storm sails, tarpaulins or protective covers: this ingenious fastener is the easiest, fastest and safest fastening solution!

The LOXX® safety lock always consists of two parts. It closes and locks automatically. The durable stainless steel spring of the upper part fits precisely around the ball head of the lower part and locks. The clever mechanism only opens when the cap of the upper part is lifted and the ball head is released. LOXX® as a safety lock is reliable in use, durable in production and surprises with its innovative design.



What is LOXX® and how does it work?

Source: esails.nl

1. LOXX BIG HEAD

The head is placed in the sail, hood or sunshade and can be attached to a self-tapping screw, piece of fabric, plate, window clip, etc.

Instructions for use:

Loxx press stud heads are very easy to attach, as they can be installed without sewing or using tools.

For elastic and soft fabrics, cut a 9 mm hole or punch it out with a punching tool. Please note that for sturdy fabrics or leather, a larger hole of 10 mm must be punched. Insert the screw thread through the hole, screw on the ring and tighten it with the small LOXX key.

2. LOXX LOWER PLATE FABRIC

The fabric piece is the opposite of the "standard" Loxx Cap. Very handy for mounting a small solar panel on the hood or connecting pieces of sail or fabric, for example.

Instructions for use:

The fabric piece is very easy to attach, as it can be installed without sewing or tools:

- 1) For elastic and soft fabrics, cut a 9 mm hole or punch it out with a punching tool. Please note that for sturdy fabrics or leather, a larger hole of 10 mm must be punched.
- 2) Insert the screw thread through the hole, screw on the ring and tighten it with the small LOXX key.

3. SELF-TAPS

The special feature of LOXX® screws is that they consist of three parts:

The screw thread is always made of saltwater-resistant stainless steel; the ball head and hexagon are made of stainless steel or nickel-plated copper.

The function of self-tapping screws is evident from their name: the screw is designed in such a way that it taps its own screw hole in the surface by making a twisting motion. We recommend pre-drilling to the thickness of the screw core.