

TECHNICAL PROPERTIES		CUBA OUTDOOR
PHYSICAL		
Width		140 cm
Length		30 m
Weight		565 gr/m2
Composition	Coating	88% PVC compound
	Backing	12% Polyester
Thickness		± 0,95 mm
STRENGTH		
Martindale	ISO 5470-2	≥ 150,000 cycles
Adhesion	ISO 2411	≥ 30 N/5 cm (warp) ≥ 30 N/5 cm (weft)
Tear strength	ISO 4674-1	≥ 24 N (warp) ≥ 30 N (weft)
Tensile strength	ISO 1421	≥ 350 N (warp) ≥ 300 N (weft)
Elongation	ISO 1421	≥ 150% (warp) ≥ 180% (weft)
Fastness to water penetration		1808 cm/H2O
Colour fastness to light	ISO 105-B02	≥ 6 (Blue Scale)
Fastness to rubbing	ISO 105-X12	
	Dry	≥ 4-5
	Wet	≥ 4-5
Colour fastness to chlorinated water	ISO 105-E03	≥ 4-5 (Grey Scale)
Colour fastness to salt water	ISO 105-E20	≥ 4-5 (Grey Scale)
SAFETY		
Flame-retardant (UK)	EN 1021, 1 & 2	Passed
Flame-retardant (IMO)	MSC.307 (88), Annex 1 Part 8	Passed
Resistance to alcohol <96%	ISO 25647	Passed
Resistance to bacteria	JIS Z 2801	Passed
Resistance to funghi	ISO 846	Passed
COMPLIANCE		
Animal Free®		Complies



Wildeman



van Leeuwen

Van Hilststraat 1 | 5145 RK Waalwijk | Netherlands

+31 (0) 416 333 651 | info@wildeman-waalwijk.nl

www.wildeman-waalwijk.nl