

TECHNICAL PROPERTIES		JOLLY FLORIDA
<b>PHYSICAL</b>		
Raw material		South American cow hides
Brand mark(s)		1-2 brand marks
Hump(s)		Possible
Substance	DIN EN ISO 2589 (IULTCS/IUP 4)	± 1,0 mm
Average size		± 5,0 m <sup>2</sup>
Dyeing		Drum dyed
Grain		Corrected Madras
<b>STRENGTH</b>		
Flexometer test	DIN EN ISO 5402 (IULTCS/IUP 402)	≥ 30.000 cycles
Tear strength	DIN EN ISO 3377-1 (IULTCS/IUP40)	≥ 20 N
Colour fastness to light	DIN EN ISO 105-B02 (IULTCS/IUF 402)	≥ 5 (Blue scale)
Colour fastness to rubbing	DIN EN ISO 11640 (IULTCS/IUF 450)	
	Dry	≥ 4, 1.000 cycles
	Wet	≥ 4, 200 cycles
	Perspiration (pH8)	≥ 4, 80 cycles
<b>SAFETY</b>		
Flame-retardant (UK)	BS 5852, 1	Passed
Flame-retardant (IMO)	A652 (16)	Passed
<b>COMPLIANCE</b>		
Reach	Free of harmful substances	Complies
ISO 14001	Environmental management	Complies
ISO 9001	Quality management	Complies
ISO TS 16949	Automotive production	Complies
IMO 0575	Marine equipment	Complies



Wildeman



van Leeuwen

Van Hilststraat 1 | 5145 RK Waalwijk | Netherlands

+31 (0) 416 650 419 | info@vanleeuwenleder.nl

[www.vanleeuwenleder.nl](http://www.vanleeuwenleder.nl)