

TECHNICAL PROPERTIES		LITANO
PHYSICAL		
Raw material		Central European bull hides
Substance	DIN EN ISO 2589 (IUP 4)	± 1,2 mm
Average size		± 5,0 m ²
Dyeing		Aniline, vacuum dried
Grain		Natural grain
STRENGTH		
Flexing endurance	ENI EN ISO 5402	No damage
Tear strength	UNI EN ISO 3377-1	≥ 20 N
Tensile strength	ISO 3376 (IULTCS/IUP 6)	≥ 20 N
Adhesion	UNI EN ISO 11644 Dry	≥ 2 N/cm
Colour fastness to light	UNI EN ISO 105-B02	≥ 5 (Blue scale)
Colour fastness to rubbing	UNI EN ISO 11640 Dry Wet	≥ 4, 500 cycles (Grey scale) ≥ 4, 250 cycles (Grey scale)
SAFETY		
Flame-retardant (UK)	BS 5852 EN 1021, 1 & 2	Passed Passed
Flame-retardant (US)	CAL TB-117 1	Passed
Flame-retardant (IMO)	A652 (16)	Passed
COMPLIANCE		
Reach	Free of harmful substances	Complies
LWG	Environmental Protocol	Gold Rated
ISO 14001	Environmental management	Complies
ISO 9001	Quality management	Complies



Wildeman



van Leeuwen

Van Hilststraat 1 | 5145 RK Waalwijk | Netherlands

+31 (0) 416 650 419 | info@vanleeuwenleder.nl

www.vanleeuwenleder.nl