

TECHNICAL PROPERTIES		NEW LASER
PHYSICAL		
Raw material		South American cow hides
Brand mark(s)		Possible
Hump(s)		Possible
Substance		± 1,5 mm
Average size		± 5,0 m ²
Dyeing		Semi aniline
Grain		Dollaro corrected
STRENGTH		
Flexometer test	(IULTCS/IUP 402)	≥ 30.000 cycles
Adhesion	EN ISO 11644	≥ 5 N/cm
Colour fastness to light	EN ISO 105-B02	≥ 5 (Blue scale)
Colour fastness to rubbing	EN ISO 11640 (IULTCS/IUF 450)	
	Dry	≥ 1.000 cycles
	Wet	≥ 200 cycles
SAFETY		
Flame-retardant (UK)	BS 5852, 1	Passed
	EN 1021, 1	Passed
Azo dye stuff	Directive 2002/61/EC	Passed
PCP	Directive 94/783/EC	Complies
COMPLIANCE		
Reach	Free of harmful substances	Complies
ISO 9001	Quality management	Complies



Wildeman



van Leeuwen

Van Hilststraat 1 | 5145 RK Waalwijk | Netherlands

+31 (0) 416 650 419 | info@vanleeuwenleder.nl

www.vanleeuwenleder.nl