

| TECHNICAL PROPERTIES        |                               | OTTOMANO                                               |                |
|-----------------------------|-------------------------------|--------------------------------------------------------|----------------|
| PHYSICAL                    |                               |                                                        |                |
| Width   Length              |                               | 152 cm   50 m                                          |                |
| Weight                      | DIN 53352                     | ± 320 gr/m2                                            |                |
| Composition                 |                               | 100% Solution dyed outdoor acrylic                     |                |
| STRENGTH                    |                               |                                                        |                |
| Abrasion Resistance         | UNI EN ISO 12947-2 Martindale | ≥ 10,000 cycles                                        |                |
| Permeability                | UNI EN ISO 24920              | ISO 5(100)                                             |                |
| Tensile strength            | UNI EN ISO 13934-1            | ≥ 1,900 N (warp)                                       | ≥ 610 N (weft) |
| Elongation                  | UNI EN ISO 13934-1            | ≥ 35,5% (warp)                                         | ≥ 13% (weft)   |
| Sewing Resistance           | UNI EN ISO 13936-2            | ≥ 4 mm (warp)                                          | ≥ 3 mm (weft)  |
| Colour fastness to light    | DIN 75202                     | ≥ 8 (Blue Scale)<br>4-5 (Grey Scale) After 1,000 hours |                |
| Shrinkage in 30 °C water    | DIN EN ISO 105-E02            | 2% (warp)                                              | 2% (weft)      |
| Pilling                     | UNI EN ISO 12945-2            | 4/2,000 cycles                                         |                |
| SAFETY                      |                               |                                                        |                |
| Flame-retardant (UK)        | BS 5852, 1                    | Passed                                                 |                |
| Resistance to oil and water |                               | Teflon finish                                          |                |