

TECHNICAL PROPERTIES		TIMOR
<b>PHYSICAL</b>		
Width		143 cm
Length		40-60 m
Weight		386 gr/m <sup>2</sup>
Composition	Coating	100% polyester
	Backing	100% polyester
<b>STRENGTH</b>		
Martindale	EN ISO 12947-1,2	≥ 80,000
Tear strength	EN ISO 13937-3	
	Warp	≥ 56,9 N (warp)
	Weft	≥ 66,3 N (weft)
Tensile strength	EN ISO 13934-1	
	Warp	≥ 893 N   25,0% (warp)
	Weft	≥ 754 N   24,5% (weft)
Colour fastness to artificial light	EN ISO 105-B02	≥ 5 (Blue Scale)
Colour fastness to rubbing	EN ISO 105-X12	
	Dry	≥ 5
	Wet	≥ 5
Resistance to pilling	EN ISO 12945-2	3-4
Resistance to seam slippage	EN ISO 13936-2	
	Warp	± 1,6 mm
	Weft	± 1,0 mm
<b>SAFETY</b>		
Flame-retardant (UK)	BS 5852-1	Passed
	EN 1021-1	Passed
Flame-retardant (US)	NFPA 260	Passed
<b>COMPLIANCE</b>		
Reach	Free of harmful substances	Complies
Blue World		Complies



Wildeman



van Leeuwen

Van Hilststraat 1 | 5145 RK Waalwijk | Netherlands

+31 (0) 416 333 651 | info@wildeman-waalwijk.nl

[www.wildeman-waalwijk.nl](http://www.wildeman-waalwijk.nl)