

TECHNICAL PROPERTIES		TRENTO+
PHYSICAL		
Raw material		European cow hides
Brand mark(s)		No
Hump(s)		No
Substance	EN ISO 2589 (IULTCS/IUP 4)	± 1,0 mm
Average size		± 5,0 m2
Dyeing		Semi aniline
Grain		Natural corrected grain
STRENGTH		
Flexometer test	ISO 5402-1 (IULTCS/IUP 20)	≥ 50,000 cycles
Tear strength	ISO 3377-1 (IULTCS/IUP40)	≥ 20 N
	ISO 3377-2 (IULTCS/IUP 8)	≥ 20 N
Tensile strength	ISO 3376 (IULTCS/IUP 6)	≥ 20 N
Adhesion	ISO 11644 (IULTCS/IUF 470)	≥ 2,5 N/cm
Colour fastness to light	ISO 105-B02	≥ 5 (Blue Scale)
Colour fastness to rubbing	ISO 11640 (IULTCS/IUF 450)	
	Dry	≥ 4, 500 cycles
	Wet	≥ 3-4, 250 cycles
	Perspiration (pH8)	≥ 3-4, 80 cycles
SAFETY		
Flame-retardant (UK)	BS 5852, 1 & 2	Passed
	EN 1021, 1 & 2	Passed
Flame-retardant	ISO 8191, 1 & 2	Passed
Flame-retardant (IMO)	A652 (16)	Passed
COMPLIANCE		
Reach	Free of harmful substances	Complies
Blue Angel	Environmental friendly	Complies
ISO 14001	Environmental management	Complies
ISO 9001	Quality management	Complies



Wildeman



van Leeuwen

Van Hilststraat 1 | 5145 RK Waalwijk | Netherlands

+31 (0) 416 650 419 | info@vanleeuwenleder.nl

www.vanleeuwenleder.nl