

TECHNICAL PROPERTIES		CUBA
PHYSICAL		
Width		140 cm
Length		30 m
Weight	DIN EN ISO 2286	± 565 gr/m ²
Composition	Coating	88% PVC compound
	Backing	12% Polyester
Thickness	DIN EN ISO 2286	± 0,95 mm
STRENGTH		
Martindale	DIN EN ISO 5470-2	≥ 150.000 cycles
Tear strength	DIN EN ISO 4674-1	
	Warp	≥ 24 N
	Weft	≥ 30 N
Tensile strength	DIN EN ISO 1421	
	Warp	≥ 350 N
	Weft	≥ 300 N
Adhesion	DIN EN ISO 2411	
	Warp	≥ 30 N/5 cm
	Weft	≥ 30 N/5 cm
Elongation	DIN EN ISO 1421	
	Warp	≥ 150%
	Weft	≥ 180%
Colour fastness to light	DIN EN ISO 105-B02	≥ 6 (Blue scale)
Colour fastness to rubbing	DIN EN ISO 105-X12	
	Dry & Wet	4-5
Colour fastness to chlorinated water	DIN EN ISO 105-E03	4-5 (Grey scale)
Colour fastness to salt water	DIN EN ISO 105-E02	4-5 (Grey scale)
Resistance to alcohol <96%	ISO 25647	Passed
SAFETY		
Flame-retardant (UK)	EN 1021, 1 & 2	Passed
Flame-retardant (IMO)	MSC.307 (88), Annex 1 Part 8	Passed
Resistance to bacteria	JIS Z 2801	Passed
Resistance to funghi	ISO 846	Passed
Resistance to hydrostatic pressure		1808 cm/H ₂ O
COMPLIANCE		
Animal Free	Free of animal derived materials	Complies



Wildeman



van Leeuwen

Van Hilststraat 1 | 5145 RK Waalwijk | Netherlands

+31 (0) 416 333 651 | info@wildeman-waalwijk.nl

www.wildeman-waalwijk.nl