

TECHNICAL PROPERTIES		SATTELLEDER
<b>PHYSICAL</b>		
Raw material		German / Austrian cow hides
Substance	EN ISO 2589 (IULTCS/IUP 4)	± 1,4 mm
Average size		± 5,0 m <sup>2</sup>
Dyeing		Full aniline
Grain		Full grain
<b>STRENGTH</b>		
Flexometer test	ISO 5402 (IULTCS/IUP 402)	≥ 50.000 cycles
Tear strength	DIN EN ISO 3377	≥ 20 N
Tensile strength	UNI ISO 3376 (IULTCS/IUP 6)	≥ 20 N
Elongation	UNI ISO 3376 (IULTCS/IUP 6)	30-70%
Colour fastness to light	ISO 105-B02	≥ 3
Colour fastness to rubbing	ISO 11640 (IULTCS/IUF 450)	
	Dry	≥ 5
	Wet	≥ 4
	Perspiration (pH8)	≥ 4
<b>SAFETY</b>		
Flame-retardant (UK)	BS 5852, 1 & 2	Passed
	EN 1021, 1 & 2	Passed
	Crib 5	Passed
Flame-retardant	ISO 8191, 1 & 2	Passed
<b>COMPLIANCE</b>		
Reach	Free of harmful substances	Complies
Blue Angel	Environmental friendly	Complies
ISO 14001	Environmental management	Complies
CO2 neutral	Environmental friendly	Complies



Wildeman



van Leeuwen

Van Hilststraat 1 | 5145 RK Waalwijk | Netherlands

+31 (0) 416 650 419 | [info@vanleeuwenleder.nl](mailto:info@vanleeuwenleder.nl)

[www.vanleeuwenleder.nl](http://www.vanleeuwenleder.nl)